

# PT 122

### **Product Information**

Application Tape based on a special high tensile impregnated paper coated with a natural rubber (Medium Tack). The tape is suitable for transferring lettering and symbols cut from all qualities of self adhesive vinyls.

Especially to be emphasised are the following properties:

- Ageing- and UV-stabilised natural rubber.
- The Application Tape is easy to unroll and position and will not stretch or curl.
- Constant adhesion within a small tolerance.
- Suitable for wet application.

## **Technical Data**

**Carrier:** Special paper,

impregnated

Adhesive: Natural rubber

**Adhesion [N/cm]:** 2,10 +/-10%

**Thickness [mm]:** 0,10 +/-5%

### **Standard Dimensions**

1.220 mm x 100 m

1.220 mm x 91,4 m

1.000 mm x 100 m

1.000 mm x 91,4 m

# **Safety Datasheet**

MSDS have not been prepared for these products, they are not subject to the MSDS requirements of the Occupational Safety and Health Administrations Hazard Communication Standard, 29 C.F.R.1910.1200 (b)(6)(v). When used under reasonable conditions and in accordance with the Poli-Tape directions for use, these products do not present a health and safety hazard. However, use or processing of the products in a manner which is not in accordance with the directions for use may affect their performance and present potential health and safety hazards.

### **POLI-TAPE Klebefolien GmbH**

Zeppelinstraße 17

53424 Remagen — GERMANY

Telefon: +49 (0) 2642 - 9836 0
Fax: +49 (0) 2642 - 9836 37
E-Mail: info@poli-tape.de
Internet: www.poli-tape.de

19/02/2010

The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material.